

# **SAFETY DATA SHEET**

Creation Date 28-Apr-2009 Revision Date 14-Feb-2020 Revision Number 3

# 1. Identification

Product Name Acetone

Cat No.: 30698

CAS-No 67-64-1 Synonyms 2-Propanone

Recommended Use Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

#### Company

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757 **Email:** tech@alfa.com

www.alfa.com

# **Emergency Telephone Number**

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660.

After normal business hours, call Carechem 24 at (866) 928-0789.

# 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2
Serious Eye Damage/Eye Irritation Category 2
Specific target organ toxicity (single exposure) Category 3

Target Organs - Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure) Category 2

Target Organs - Kidney, Liver, spleen, Blood.

# Label Elements

#### Signal Word

Danger

#### **Hazard Statements**

Highly flammable liquid and vapor Causes serious eye irritation May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure



### **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

#### Response

Get medical attention/advice if you feel unwell

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eve irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

#### **Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Acetone	67-64-1	>95

# 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

Revision Date 14-Feb-2020 Acetone

call a physician.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Clean mouth with water and drink afterwards plenty of water. Ingestion

Most important symptoms and

effects

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema

Treat symptomatically Notes to Physician

# 5. Fire-fighting measures

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

**Unsuitable Extinguishing Media** Water may be ineffective

**Flash Point** -20 °C / -4 °F

Method -CC (closed cup)

**Autoignition Temperature** 465 °C / 869 °F

**Explosion Limits** 

Upper 12.8 vol % Lower 2.5 vol % **Oxidizing Properties** Not oxidising

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### **Specific Hazards Arising from the Chemical**

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Formaldehyde. Methanol.

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health **Flammability** Instability Physical hazards 2 3 N/A

# Accidental release measures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all **Personal Precautions** 

sources of ignition. Take precautionary measures against static discharges.

Should not be released into the environment. **Environmental Precautions** 

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Up

# 7. Handling and storage

Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid

ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

**Storage** 

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

# 8. Exposure controls / personal protection

# **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Acetone	TWA: 250 ppm	(Vacated) TWA: 750 ppm	IDLH: 2500 ppm	TWA: 500 ppm
	STEL: 500 ppm	(Vacated) TWA: 1800 mg/m <sup>3</sup>	TWA: 250 ppm	STEL: 750 ppm
		(Vacated) STEL: 2400	TWA: 590 mg/m <sup>3</sup>	
		mg/m³	_	
		(Vacated) STEL: 1000 ppm		
		TWA: 1000 ppm		
		TWA: 2400 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations

and safety showers are close to the workstation location. Use explosion-proof

electrical/ventilating/lighting/equipment.

**Personal Protective Equipment** 

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorsweetOdor Threshold19.8 ppmpH7

 Melting Point/Range
 -95 °C / -139 °F

 Boiling Point/Range
 56 °C / 132.8 °F

 Flash Point
 -20 °C / -4 °F

 Method CC (closed cup)

**Evaporation Rate** 5.6 (Butyl Acetate = 1.0) **Flammability (solid,gas)** Not applicable

Flammability or explosive limits

 Upper
 12.8 vol %

 Lower
 2.5 vol %

Vapor Pressure 247 mbar @ 20 °C

Vapor Density 2.0

Revision Date 14-Feb-2020

Acetone

Specific Gravity 0.790

SolubilitySoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature465 °C / 869 °F

Decomposition Temperature > 4°C

Viscosity 0.32 mPa.s @ 20 °C

Molecular FormulaC3 H6 OMolecular Weight58.08Refractive index1.358 - 1.359

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Heat, flames and sparks. Incompatible products. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong reducing agents, Strong bases, Peroxides, Halogenated

compounds, Alkali metals, Amines

Hazardous Decomposition Products Carbon monoxide (CO<sub>2</sub>), Formaldehyde, Methanol

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions**None under normal processing.

# 11. Toxicological information

#### **Acute Toxicity**

#### **Product Information**

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit)	76 mg/l, 4 h, (rat)
		> 7400 ma/ka (rat)	

Toxicologically Synergistic Products

Carbon tetrachloride; Chloroform; Trichloroethylene; Bromodichloromethane; Dibromochloromethane; N-nitrosodimethylamine; 1,1,2-Trichloroethane; Styrene;

Acetonitrile, 2,5-Hexanedione; Ethanol; 1,2-Dichlorobenzene

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes

Sensitization No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Γ	Acetone	67-64-1	Not listed				

Mutagenic Effects No information available

Reproductive Effects

No information available.

Developmental Effects

No information available.

**Teratogenicity** No information available.

**STOT - single exposure**STOT - repeated exposure
Central nervous system (CNS)
Kidney Liver spleen Blood

Aspiration hazard No information available

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting:

delayed May cause pulmonary edema

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

#### **Ecotoxicity**

.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	NOEC = 430 mg/l (algae; 96	Oncorhynchus mykiss: LC50	EC50 = 14500 mg/L/15 min	EC50 = 8800 mg/L/48h
	h)	= 5540 mg/l 96h		EC50 = 12700 mg/L/48h
		Alburnus alburnus: LC50 =		EC50 = 12600 mg/L/48h
		11000 mg/l 96h		
		Leuciscus idus: LC50 =		
		11300 mg/L/48h		
		Salmo gairdneri: LC50 =		
		6100 mg/L/24h		

Persistence and Degradability Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow		
Acetone	-0.24		

Other adverse effects None known

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-

# 14. Transport information

DOT

UN-No UN1090
Proper Shipping Name ACETONE

Hazard Class 3
Packing Group ||

**TDG** 

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group |

<u>IATA</u>

**UN-No** UN1090

Proper Shipping Name ACETONE

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3 Packing Group II

# 15. Regulatory information

#### United States of America Inventory

Component	CAS-No TSCA		TSCA Inventory notification - Active/Inactive	TSCA - EPA Regulatory Flags	
Acetone	67-64-1	X	ACTIVE	-	

Legend:

TSCA - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed '-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

#### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

Component	CAS-No	DSL	NDSL	EINECS	PICCS	ENCS	AICS	IECSC	KECL
Acetone	67-64-1	X	-	200-662-2	X	X	X	X	KE-29367

# U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

Health Administration

Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs	
Acetone	5000 lb	-	

California Proposition 65 This product does not contain any Proposition 65 chemicals.

# U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X	-	X

### **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

This product does not contain any DHS chemicals.

Security

#### Other International Regulations

Mexico - Grade Serious risk, Grade 3

16. Other information

Prepared By Health, Safety and Environmental Department

Email: tech@alfa.com

www.alfa.com

 Creation Date
 28-Apr-2009

 Revision Date
 14-Feb-2020

 Print Date
 14-Feb-2020

**Revision Summary** SDS authoring systems update, replaces ChemGes SDS No. 67-64-1.

# Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**