



**BRAVO 1500+ UHS Floor Stripper**

HMIS		NFPA	Personal protective equipment
Health	3	3	
Fire Hazard	0	0	
Reactivity	0	0	

Version Number: 0

Preparation date: 2011-09-28

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name:** BRAVO 1500+ UHS Floor Stripper

**MSDS #:** MS0300876  
**Product Code:** 5594995  
**Recommended use:** Industrial/Institutional. Floor stripper. This product is intended to be diluted prior to use.

**Manufacturer, importer, supplier:**  
 US Headquarters  
 Diversey, Inc.  
 8310 16th St.  
 Sturtevant, Wisconsin 53177-1964  
 Phone: 1-888-352-2249  
 MSDS Internet Address: www.diversey.com

Canadian Headquarters  
 Diversey, Inc. - Canada  
 2401 Bristol Circle  
 Oakville, Ontario L6H 6P1  
 Phone: 1-800-668-3131

**Emergency telephone number:** 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

DANGER. CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED.

**Principal routes of exposure:** Eye contact. Skin contact. Inhalation.  
**Eye contact:** Corrosive. Causes permanent eye damage, including blindness.  
**Skin contact:** Corrosive. Causes permanent damage.  
**Inhalation:** May cause irritation and corrosive effects to nose, throat and respiratory tract.  
**Ingestion:** Corrosive. Causes burns to mouth, throat and stomach.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredient(s)	CAS #	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
Benzyl alcohol	100-51-6	5 - 10%	1230	2000 mg/kg	8.8 mg/L (4 h)
Diethylene glycol butyl ether	112-34-5	1 - 5%	4500	2700 mg/kg	Not available
Monoethanolamine	141-43-5	10 - 20%	1720	1 mL/kg 1025 mg/kg	Not available

**4. FIRST AID MEASURES**

**Eye contact:** Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical attention immediately.

**Skin contact:** Immediately flush with plenty of water for 15-20 minutes. Get medical attention immediately.

**Inhalation:** If breathing is affected, remove to fresh air. Get medical attention immediately.

**Ingestion:** If swallowed, rinse mouth. Give a cupful of water or milk. THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

**Aggravated Medical Conditions:** Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects

**5. FIRE-FIGHTING MEASURES**

**Suitable extinguishing media:** The product is not flammable. Extinguish fire using agent suitable for surrounding fire.  
**Specific hazards:** Not applicable  
**Unusual hazards:** None known  
**Specific methods:** No special methods required

**Special protective equipment for firefighters:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

**Extinguishing media which must not be used for safety reasons:** No information available

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Use personal protective equipment  
**Environmental precautions and clean-up methods:** No information available

## 7. HANDLING AND STORAGE

**Handling:**  
 Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

**Storage:**  
 Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering measures to reduce exposure:**  
 Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

### Personal Protective Equipment

**Eye protection:** Chemical-splash goggles.  
**Hand protection:** Chemical-resistant gloves  
**Skin and body protection:** Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.  
**Respiratory protection:** In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.  
**Hygiene measures:** Handle in accordance with good industrial hygiene and safety practice

Ingredient(s)	CAS #	ACGIH	OSHA	Mexico
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m <sup>3</sup> (TWA)	6 ppm (STEL) 15 mg/m <sup>3</sup> (STEL) 3 ppm (TWA) 8 mg/m <sup>3</sup> (TWA)

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<p><b>Physical State:</b> Liquid  <b>Appearance:</b> Aqueous solution  <b>Specific gravity:</b> 1.016  <b>Vapor density:</b> No information available  <b>Boiling point/range:</b> Not determined  <b>Decomposition temperature:</b> Not determined  <b>Solubility:</b> Completely Soluble  <b>Solubility in other solvents:</b> No information available  <b>Partition coefficient (n-octanol/water):</b> No information available  <b>Elemental Phosphorus:</b> 0.00 % by wt.  <b>pH:</b> 12.1  <b>Explosion limits:</b> - upper: Not determined - lower: Not determined</p>	<p><b>Bulk density:</b> No information available  <b>Evaporation Rate:</b> No information available  <b>Color:</b> Clear Straw  <b>Odor:</b> Solvent Solvent  <b>Melting point/range:</b> Not determined  <b>Autoignition temperature:</b> No information available  <b>Density:</b> 8.51 lbs/gal 1.02 Kg/L  <b>Flash point:</b> &gt; 200 °F &gt; 93.4 °C  <b>Viscosity:</b> No information available  <b>VOC:</b> 11.25 % *  <b>Dilution pH:</b> 11.45 @ 1:4</p>
--	---

\* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

## 10. STABILITY AND REACTIVITY

**Stability:** The product is stable  
**Polymerization:** Hazardous polymerization does not occur  
**Hazardous decomposition products:** None reasonably foreseeable.

## 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:** Corrosive. Oral LD50 estimated to be between 4000 - 5000 mg/kg ; Dermal LD50 estimated to be > 2000 mg/kg  
**Component Information:** See Section 3  
**Chronic toxicity:** None known  
**Specific effects**  
**Carcinogenic effects:** None known  
**Mutagenic effects:** None known  
**Reproductive toxicity:** None known  
**Target organ effects:** None known

## 12. ECOLOGICAL INFORMATION

**Environmental Information:** No data available

## 13. DISPOSAL CONSIDERATIONS

**Waste from residues / unused products:**

This product, as sold, if discarded or disposed, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations

**RCRA Hazard Class:** Not Regulated

## 14. TRANSPORT INFORMATION

**DOT/TDG/IMDG:** Please refer to the Diversey HazMat Library, <http://naextranet.diversey.com/dot/>, for up to date shipping information.

**DOT Bill of Lading Description:** UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S., (MONOETHANOLAMINE, BENZYL ALCOHOL), 8, II

**IMDG Bill of Lading Description:** Same as DOT above.

## 15. REGULATORY INFORMATION

**International Inventories at CAS# Level**

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

**U.S. Regulations**

**California Proposition 65:** This product is not subject to the reporting requirements under California's Proposition 65

**RIGHT TO KNOW (RTK)**

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Benzyl alcohol	100-51-6	X	-	X	-
Diethylene glycol butyl ether	112-34-5	-	-	-	-
Sodium xylene sulfonate	1300-72-7	-	-	-	-
Monoethanolamine	141-43-5	X	X	X	X
Water	7732-18-5	-	-	-	-

**CERCLA/ SARA**

**SARA 311/312 Hazard Categories**

**Immediate:** X

Delayed: -  
Fire: -  
Reactivity: -  
Sudden Release of Pressure: -

**Canada**

WHMIS hazard class: E Corrosive material



**16. OTHER INFORMATION**

**Reason for revision:** Not applicable  
**Prepared by:** NAPRAC  
**Additional advice:** None

*Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.*