



Buckeye International, Inc.
2700 Wagner Place
Maryland Heights, MO 63043
314/291-1900

N. F. P. A.

4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant

	HEALTH	0
	FLAMMABILITY	0
	INSTABILITY	0

Material Safety Data Sheet

24 Hour Medical Emergency Telephone Number: 1-800-303-0441. Outside North America call : 651-632-8956.

24 Hour Transportation Emergency Telephone Number: 1-800-535-5053. Outside North America call : 352-323-3500.

SECTION I - IDENTIFICATION				
PRODUCT NAME SYMMETRY NON ALCOHOL FOAMING HAND SANITIZER			DATE PREPARED March 15, 2012	
CHEMICAL FAMILY Hand Sanitizer			CODE 9015	
PROPER D.O.T.				
SHIPPING NAME Toilet Preparations				
D.O.T. HAZARD				
CLASSIFICATION None				
SECTION II - INGREDIENTS AND IDENTITY INFORMATION				
% By WGT	MATERIAL	PEL	T.L.V.	C.A.S. NO.
0.12	Benzalkonium Chloride	NE	NE	68424-85-1
>96.76	Distilled Water	NE	NE	7732-18-5
<3.0	Perfume and Additives less than 1%	NE	NE	Blend
ITEMS MARKED * ARE SARA TITLE III SEC 313 REPORTABLES. ALL INGREDIENTS ARE ON TSCA INVENTORY.				
SECTION III - PHYSICAL DATA				
BOILING POINT °F	212° F	pH (CONC.)	7.8 ± 0.5	
SOLUBILITY IN WATER	Miscible	pH (USE DILUTION) RTU	7.8 ± 0.5	
% VOLATILE BY WEIGHT	>95.0	EVAPORATION RATE (WATER =1)	1.0	
SPECIFIC GRAVITY	1.00	PRODUCT FORM	Liquid	
APPEARANCE AND ODOR	Clear solution, Fruity floral fragrance			
SECTION IV - FIRE AND EXPLOSION DATA				
FLASH POINT (Test Method)	None -- Tagged Closed Cup	FLAMMABLE LIMITS		
EXTINGUISHING MEDIA	NA	UPPER LIMIT: NA	LOWER LIMIT: NA	
SPECIAL FIRE FIGHTING PROCEDURES	None			
UNUSUAL FIRE AND EXPLOSION HAZARDS	Products of combustion			
Oxides of carbon				
SECTION V - REACTIVITY DATA				
STABILITY	Stable			
CONDITIONS TO AVOID	None known.			
INCOMPATIBILITY	Do not mix with chlorine bleach.			
HAZARDOUS DECOMPOSITION PRODUCTS	None known.			
HAZARDOUS POLYMERIZATION	Will not occur.			

SYMMETRY NON ALCOHOL FOAMING HAND SANITIZER CODE: 9015

SECTION VI - HEALTH HAZARD DATA			
ROUTE(S) OF ENTRY:		INHALATION? NO	SKIN? YES
		INGESTION? NO	
HEALTH HAZARDS (Acute and Chronic)			
May cause eye irritation.			
CARCINOGENICITY:		NTP? No	IARC MONOGRAPHS? NO
		OSHA REGULATED? No	
SIGNS AND SYMPTOMS OF OVEREXPOSURE			
Eyes: Redness or burning sensation.			
MEDICAL CONDITIONS			
GENERALLY AGGRAVATED BY EXPOSURE			
None known.			
EMERGENCY AND FIRST AID PROCEDURES			
For Eyes: Flush with cool water for 15 minutes. If irritation occurs and persists, see physician.			
For Ingestion: Give two large glasses of water. DO NOT induce vomiting. Call physician.			
Never give anything by mouth to an unconscious person.			
SECTION VII - SPILL OR LEAK PROCEDURES			
SPILL RESPONSE			
Will cause slippery surfaces.			
Pick up with mop, wet/dry vac or absorbent material. Rinse area with clear water and allow floor to dry before allowing traffic.			
WASTE DISPOSAL			
METHOD		Flush to sanitary sewer or send to sanitary landfill, following local, state and federal laws.	
SECTION VIII - SPECIAL PROTECTION INFORMATION			
EYE PROTECTION		VENTILATION	
None required.		Normal room ventilation.	
SKIN PROTECTION		RESPIRATORY PROTECTION	
None required.		None required.	
OTHER PROTECTION		Follow good personal hygiene practices.	
SECTION IX - SPECIAL PRECAUTIONS			
PRECAUTIONS IN HANDLING AND STORAGE		KEEP OUT OF REACH OF CHILDREN!	
		Keep container closed when not in use.	
		Store at room temperature. Avoid freezing conditions.	
OTHER PRECAUTIONS		This product is not regulated under CERCLA or RCRA.	
		Not reportable under SARA Title III, Section 311/312.	
NA = Not Applicable		Complies with current FDA regulations for cosmetic and/or over-the-counter drug products.	
NE = Not Established			
PREPARED BY:		Scott Maag, Vice President of Operations	
Disclaimer of Liability			
As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material.			
Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Conforms to OSHA 174, Sept 1985.			