THOMPSON AND FORMBY INC -- THOMPSON'S WATER SEAL, WATERPROOFING FORMULA ______ MSDS Safety Information _____ FSC: 8030 NIIN: 00-555-2878 MSDS Date: 02/11/1994 MSDS Num: BJQTC Product ID: THOMPSON'S WATER SEAL, WATERPROOFING FORMULA MFN: 01 Responsible Party Cage: 63727 Name: THOMPSON AND FORMBY INC Address: 825 CROSSOVER LANE City: MEMPHIS TN 38117 Info Phone Number: 901-685-7555 Emergency Phone Number: 201-573-5700 800-424-9300 Review Ind: Y Published: Y _____ Contractor Summary _____ Cage: 63727 Name: THOMPSON AND FORMBY INC Address: 825 CROSSOVER LN SUITE 240 BLDG C City: MEMPHIS TN 38117-4934 Phone: 901-685-7555 ______ Item Description Information _____ Item Manager: GSA Item Name: SEALING COMPOUND Specification Number: NONE Type/Grade/Class: NONE Unit of Issue: GL UI Container Qty: 1 GALLON Type of Container: CAN ______

Ingredients

Cas: 64742-88-7

RTECS #: 1003692SN

Name: SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC

% Wt: 75-80

OSHA PEL: 5 MG/M3 (OIL MIST) ACGIH TLV: 5 MG/M3 (OIL MIST)

Health Hazards Data

LD50 LC50 Mixture: LD50 (ORAL RAT) IS UNKNOWN

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: INHALED:AVOID PROLONGED BREATHING OF VAPORS. DO

NOT

BREATHE SPRAY MIST. SKIN: AVOID PROLONGED OR REPEATED CONTACT W/

SKIN. EYE: WEAR

EYE PROTECTION TO AVOID CONTACT W/EYES. INGESTED: HARMFUL OR FATAL IF SWALLOWED. INTENTIONAL MISUSE BY DELIBERA TELY CONCENTRATING AND

INHLAING THE

CONTENTS MAY BE HARMFUL OR FATAL.

Explanation Of Carcinogenicity: MANUFACTURER GAVE NO COMMENTS OTHER THAN THE

ABOVE REFERENCES TO THE THREE LISTINGS.

Signs And Symptions Of Overexposure: IF YOU EXPERIENCE EYE WATERING, HEADACHE,

DIZZINESS; INCREASE AIR, WEAR RESPIRATORY PROTECTION OR LEAVE AREA.

Medical Cond Aggravated By Exposure: PRI-EXISTING EYE, SKIN AND RESPIRATORY

DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid: INHALED: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO

FRESH AIR. SKIN: IN KEEPING W/GOOD HYGIENIC PRACTICE, WASH THOROUGHLY W/SOAP

& WATER. EYE:IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY W/PLENTY OF WATER.

INGESTED: IF SWALLOWED, DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL

ATTENTION.

Handling and Disposal

Spill Release Procedures: ABSORB WITH SAND OR OTHER SUITABLE ABSORBENT MATERIAL. THEN PLACE IN A CONTAINER FOR DISPOSAL.

Neutralizing Agent: MFR GAVE NO INFORMATION ON MSDS.

Waste Disposal Methods: VEST DISPOSAL IS BY CONSUMING THROUGH INGENDED USE.

DISPOSE OF EXCESS PRODUCT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL

REGULATIONS GOVERNING COMBUSTIBLE WASTE.

Handling And Storage Precautions: CONTAINS PETROLEUM DISTILLATES. DO NOT USE

NEAR SPARKS, HEAT OR FLAME. AVOID PROLONGED BREATHING OF VAPORS. DO NOT

BREATHE SPRAY MIST.

Other Precautions: USE IN WELL VENTILATED AREA. OPEN WINDOWS AND DOORS ORUSE

OTHER MEANS TO INSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. IFYOU

EXPERIENCE EYE WATERING, HEADACHE OR DIZZINESS, INCREASE FRESH AIR, SEARRESPIRATOR OR LEAVE AREA.

Fire and Explosion Hazard Information

Flash Point Method: SCC

Flash Point Text: <101F, <38C

Lower Limits: 1.0 Upper Limits: 6.0

Extinguishing Media: USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE. DO

NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT & REIGNITE. Fire Fighting Procedures: TO ENTER CONFINED FIRE SPACE USE FULL BUNKER GEAR

W/POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL

FIRE EXPOSED CONTAINERS W/WATER.

Unusual Fire/Explosion Hazard: COMBUSTIBLE! DO NOT USE NEAR SPARKS, HEAT, FLAME.

FIRE EXPOSED CONTAINERS SHOULD BE COOLED W/WTO PREVENT RUPTURE.

Control Measures

Respiratory Protection: DO NOT BREATHE SPRAY MIST. IF YOU EXPERIENCE

```
EYE
```

WATERING, HEADACHE OR DIZZINESS, INCREASE FRESH AIR, WEAR RESPIRATOR (NIOSH/MSHA TC23C OR EQUIVALENT APPROVED) OR LEAVE AREA.

Ventilation: AVOID PROLONGED BREATHING OF VAPORS. USE IN WELL VENTILATED AREA.

OPEN DOORS & WINDOWS TO ENSURE FRESH AIR DURING USE.

Protective Gloves: AVOID PROLONGED/REPEATED SKIN CONTACT

Eye Protection: WEAR EYE PROTECTION. PREVENT EYE CONTACT

Other Protective Equipment: NONE REQUIRED

Work Hygienic Practices: USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID ALL

UNNECESSARY EXPOSURE. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health: NONE

Physical/Chemical Properties

HCC: F4

NRC/State LIC No: NONE

Net Prop WT For Ammo: NONE

B.P. Text: 318F,159C M.P/F.P Text: UNKNOWN Decomp Text: UNKNOWN

Vapor Pres: <55

Vapor Density: 4.8 Spec Gravity: 0.80

Evaporation Rate & Reference: UNKNOWN

Solubility in Water: INSOLUBLE

Appearance and Odor: AMBER MOBILE LIQUID, PETROLEUM SOLVENT ODOR

Percent Volatiles by Volume: 85

Corrosion Rate: UNKNOWN

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: DO NOT USE NEAR HEAT, SPARK, FLAMES.

Materials To Avoid: STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: WILL NOT OCCUR.

Toxicological Information

Ecological Information ______ ______ MSDS Transport Information _____ ______ Regulatory Information ______ ______ Other Information ______ ______ Transportation Information ______ Responsible Party Cage: 63727 Trans ID NO: 76672 Product ID: THOMPSON'S WATER SEAL, WATERPROOFING FORMULA MSDS Prepared Date: 02/11/1994 Review Date: 12/31/1994 MFN: 1 Net Unit Weight: UNKNOWN Multiple KIT Number: 0 Review IND: Y Unit Of Issue: GL Container QTY: 1 GALLON Type Of Container: CAN Additional Data: THE PRODUCT IS CLASSIFIED AS A PAINT, P.G. III. HOWEVER IF SHIPPING DOMESTICALLY, IT QUALIFIES AS A COMBUSTIBLE LIQUID WHICH IS NOT REGULATED IN ONE GALLON SIZES. ______ Detail DOT Information ______ DOT PSN Code: XXX ______ Detail IMO Information ______ IMO PSN Code: LCT IMO Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL IMO PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS, VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR

```
(INCLUDING PAINT
 THINNING OR REDUCING COMPOUND) o
IMDG Page Number: 3372
UN Number: 1263
UN Hazard Class: 3.3
IMO Packaging Group: III
Subsidiary Risk Label: -
EMS Number: 3-05
MED First Aid Guide NUM: 310
______
Detail IATA Information
______
IATA PSN Code: SXH
IATA UN ID Num: 1263
IATA Proper Shipping Name: PAINT
IATA PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC,
VARNISH,
 POLISH, LIQUID FILLER AND LIQUID LACQUER BASE)
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
UN Packing Group: III
Packing Note Passenger: 309
Max Quant Pass: 60L
Max Quant Cargo: 220L
Packaging Note Cargo: 310
______
Detail AFI Information
_____
AFI PSN Code: SXH
AFI Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL
AFI PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC
SOLUTIONS,
 VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR
(INCLUDIN PAINT
 THINNING OR REDUCING COMPOUNDS)
AFI Hazard Class: 3
AFI UN ID NUM: UN1263
AFI Packing Group: III
Special Provisions: P5
Back Pack Reference: A7.3
_____
HAZCOM Label
______
```

Product ID: THOMPSON'S WATER SEAL, WATERPROOFING FORMULA

Cage: 63727

Company Name: THOMPSON AND FORMBY INC

Street: 825 CROSSOVER LN SUITE 240 BLDG C

City: MEMPHIS TN Zipcode: 38117-4934

Health Emergency Phone: 901-685-7555

Label Required IND: Y

Date Of Label Review: 12/31/1994

Status Code: C

MFG Label NO: NONE

Label Date: 12/31/1994

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: YES

Health Hazard: Moderate Contact Hazard: Slight Fire Hazard: Moderate Reactivity Hazard: None

Hazard And Precautions: **TARGET ORGANS:SKIN, EYES, RESPIRATORY

SYSTEM, CNS **

INHALED: AVOID PROLONGED BREATHING OF VAPORS. DO NOT BREATHE SPRAY MIST.

SKIN:AVOID PROLONGED OR REPEATED CONTACT W/SKIN. EYE:WEAR EYE PROTECTION TO

AVOID CONTACT W/EYES. INGESTED: HARM FUL OR FATAL IF SWALLOWED.

INTENTIONAL

MISUSE BY DELIBERATELY CONCENTRATING AND INHLAING THE CONTENTS MAY BE HARMFUL

OR FATAL. CONTAINS PETROLEUM DISTILLATES. DO NOT USE NEAR SPARKS, HEAT OR

FLAME. AVOID PROLONGED BREATHING OF VAPORS. DO NOT BREATHE SPRAY MIST. IN

CASE OF SPILL: ABSORB WITH SAND OR OTHER SUITABLE ABSORBENT MATERIAL. THEN

PLACE IN A CONTAINER FOR DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This

information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or

viability by or to any person or persons outside the Department of Defense

nor any person or persons contracting with any instrumentality of the United

States of America and disclaims all liability for such use. Any person

utilizing this instruction who is not a military or civilian employee of the

United States of America should seek competent professional advice to verify

and assume responsibility for the suitability of this information to their

particular situation regardless of similarity to a corresponding Department

of Defense or other government situation.